Volthium

Alimentez le futur
Powering the future

TECHNICAL SHEET
12 V 130 Ah



Volthium Energy inc. | T. 514.989.9586 | info@volthium.com | www.volthium.com

Volthium
Alimentez le futur
Powering the future

Before using your Volthium battery, please read the user manual and the datasheet specific to your battery.
You can find these documents by clicking on the following link: https://volthium.com/en/documents/
Any improper use of the product may void its warranty.
For any additional questions, please contact Volthium technical support.

ELECTRICAL SPECIFICATIONS	
Voltage	12.8 volt
Capacity	130 Ah
Capacity @ 20A	390 min
Energy	1664 Wh
Self-discharge	< 3% per month
Maximum unit in series	4
Maximum unit in parallel	4

CHARGE SPECIFICATIONS	
Recommended charge current	5 A - 50 A
Maximum charge current	100 A
Recommended charge voltage	14.2 V - 14.6 V (Bulk) | 13.6 V (Float)

DISCHARGE SPECIFICATIONS	
Continuous discharge current	100 A
BMS – Discharge disconnect voltage	10 V
BMS – Discharge reconnection voltage	12 V
Short circuit protection	Yes

TEMPERATURE SPECIFICATIONS	
Discharge temperature	From -30 to 60°C
Charging temperature	From 0 to 45°C

STORAGE SPECIFICATIONS	
Storage temperature	From -20 to 45°C
Storage voltage	From 13.1 V to 13.3 V


COMMUNICATIONS SPECIFICATIONS	
Bluetooth	Optional
Communication ports	RS485
LCD screen	No
Volthium CAN Hub Communication (VE.CAN)	Compatible


HEATING SPECIFICATIONS	
Activation temperature	From -35 to 11°C
Activation current	6 A
Heating current	3 A
System activation mode	Automatic

NUMBER OF CYCLES ACCORDING TO THE AVERAGE DISCHARGE % OF USE	
30% discharge	8200 < cycles
80% discharge	6000 < cycles
100% discharge	3500 < cycles

MECHANICAL SPECIFICATIONS	
Dimensions	260 X 168 X 229 mm | 10.24 X 6.61 X 9 po
Group / format	GR24
Weight	15kg | 33 lbs
Terminal Type	M8
Tightening torque on terminals	N/A
Ingress protection rating	IP55 (Against low-pressure water jets and dust)

CERTIFICATIONS & DESIGN	
Design	4S2P
Certifications	Battery UL2054 | Cells UL1973
Shipping classification	UN 3480 | CLASS 9
Cell type	SquareCell - LiFePO4 - 67 Ah - 3.2 V - Grade A+


260.0000
229.0000
225.0000


168.0000

