Volthium

Alimentez le futur
Powering the future

TECHNICAL SHEET
24 V 200 Ah - RACKMOUNT 3U



Volthium Energy inc. | T. 514.989.9586 | info@volthium.com | www.volthium.com

Volthium
Alimentez le futur
Powering the future

Before using your Volthium battery, please read the user manual and the datasheet specific to your battery.
You can find these documents by clicking on the following link: https://volthium.com/en/documents/
Any improper use of the product may void its warranty.
For any additional questions, please contact Volthium technical support.

ELECTRICAL SPECIFICATIONS	
Voltage	25.6 volt
Capacity	200 Ah
Capacity @ 20A	600 min
Energy	5120 Wh
Self-discharge	< 1% per month
Maximum unit in series	0
Maximum unit in parallel	32

CHARGE SPECIFICATIONS	
Recommended charge current	≤50 A
Maximum charge current	70 A
Recommended charge voltage	28 V (Bulk) | 27.3 V (Float)

DISCHARGE SPECIFICATIONS	
Continuous discharge current	100 A
BMS – Discharge disconnect voltage	24 V
BMS – Discharge reconnection voltage	26 V
Short circuit protection	Yes
Peak discharge current	119 for 5 minutes | 200 A for 3 sec

TEMPERATURE SPECIFICATIONS	
Discharge temperature	From -10 to 50°C
Charging temperature	From -10 to 50°C

STORAGE SPECIFICATIONS	
Storage temperature	From -10 to 45°C
Storage voltage	From 26.2 V to 26.6 V


COMMUNICATIONS SPECIFICATIONS	
Bluetooth	No
Communication ports	2x RS485 | 2x Batt. Com. | 1x CAN
LCD screen	No
Volthium CAN Hub Communication (VE.CAN)	Compatible


HEATING SPECIFICATIONS	
Activation temperature	from -25°C to 5°C
Activation current	5 A
Heating current	4 A
System activation mode	Automatic


NUMBER OF CYCLES ACCORDING TO THE AVERAGE DISCHARGE % OF USE	
30% discharge	8200 < cycles
80% discharge	6000 < cycles
100% discharge	3500 < cycles

MECHANICAL SPECIFICATIONS	
Dimensions	482 X 133.5 X 460 mm | 18.9 X 5.2 X 18.1 po
Group / format	3U
Weight	46kg | 101 lbs
Terminal Type	M10
Tightening torque on terminals	8~10nm / 6-8 ft/lb
Ingress protection rating	IP20 (Against solid objects larger than 12 mm)

CERTIFICATIONS & DESIGN	
Design	8S2P
Certifications	ETL UL1973 3rd Edition / UL9540A / Full battery SPE-1000 ($)
Shipping classification	UN 3480 | CLASS 9
Cell type	SquareCell - LiFePO4 - 3.2 V - 100 Ah


Volthium
51.2-100-R
133


529.5
441
482.6


490
540