Volthium

Alimentez le futur
Powering the future

TECHNICAL SHEET
RACKMOUNT 10KW
51.2 V 200 Ah



Volthium Energy inc. | T. 514.989.9586 | info@volthium.com | www.volthium.com

Volthium
Alimentez le futur
Powering the future

Before using your Volthium battery, please read the user manual and the datasheet specific to your battery.
You can find these documents by clicking on the following link: https://volthium.com/en/documents/
Any improper use of the product may void its warranty.
For any additional questions, please contact Volthium technical support.

ELECTRICAL SPECIFICATIONS	
Voltage	51.2 volt
Capacity	200 Ah
Capacity @ 20A	600 min
Energy	10240 Wh
Self-discharge	< 1% per month
Maximum unit in series	Contact us
Maximum unit in parallel	16 (per bank) x 5 banks

CHARGE SPECIFICATIONS	
Recommended charge current	100 A
Maximum charge current	125 A
Recommended charge voltage	56 V (Bulk) | 54.4 V (Float)

DISCHARGE SPECIFICATIONS	
Continuous discharge current	125 A
BMS – Discharge disconnect voltage	43.2 V
BMS – Discharge reconnection voltage	48 V
Short circuit protection	Yes

TEMPERATURE SPECIFICATIONS	
Discharge temperature	From -20 to 65°C
Charging temperature	From 0 to 45°C

STORAGE SPECIFICATIONS	
Storage temperature	From -20 to 45°C
Storage voltage	From 52.4 V to 53.6 V


COMMUNICATIONS SPECIFICATIONS	
Bluetooth	No
Communication ports	2x RS485 | 2x Batt. Com. | 1x CAN
LCD screen	No
Volthium CAN Hub Communication (VE.CAN)	Compatible


HEATING SPECIFICATIONS	
Activation temperature	From -30 to 11°C
Activation current	8 A
Heating current	5.5 A
System activation mode	Automatic

NUMBER OF CYCLES ACCORDING TO THE AVERAGE DISCHARGE % OF USE	
30% discharge	8200 < cycles
80% discharge	6000 < cycles
100% discharge	3500 < cycles

MECHANICAL SPECIFICATIONS	
Dimensions	465 X 680 X 222 mm | 19 X 27 X 8.7 po
Group / format	5U
Weight	94kg | 208 lbs
Terminal Type	M8 OR Surlok (SLPPB35BNO)
Tightening torque on terminals	8~10nm / 6-8 ft/lb
Ingress protection rating	IP20 (Against solid objects larger than 12 mm)

CERTIFICATIONS & DESIGN	
Design	16S2P
Certifications	Full Pack Assembly CSA UL1973 3rd Edition | Cells UL1973 & CSA UL9540A | IEC62619 | IEC62660 |Breaker UL1077@CSAC22.2 No. 235-04 | Terminal UL1977
Shipping classification	UN 3480 | CLASS 9
Cell type	SquareCell - LiFePO4


465
222
175
45
Volthium
51.2V200Ah


442
680

