Volthium

Alimentez le futur
Powering the future

TECHNICAL SHEET
RACKMOUNT 3U
51.2 V 100 Ah



Volthium Energy inc. | T. 514.989.9586 | info@volthium.com | www.volthium.com

Volthium
Alimentez le futur
Powering the future

Before using your Volthium battery, please read the user manual and the datasheet specific to your battery.
You can find these documents by clicking on the following link: https://volthium.com/en/documents/
Any improper use of the product may result in the invalidation of its 10-year warranty.
For any additional questions, please contact Volthium technical support.

ELECTRICAL SPECIFICATIONS	
Voltage	51.2 volt
Capacity	100 Ah
Capacity @ 20A	300 min
Energy	5120 Wh
Self-discharge	< 3% per month
Maximum unit in series	Contact us
Maximum unit in parallel	32

CHARGE SPECIFICATIONS	
Recommended charge current	70 A
Maximum charge current	100 A
Recommended charge voltage	56 V (Bulk) | 54.6 V (Float)

DISCHARGE SPECIFICATIONS	
Continuous discharge current	100 A
BMS – Reconnection voltage	43.2 V ~ 45 V
BMS – Discharge reconnection voltage	52 V
Short circuit protection	Yes

TEMPERATURE SPECIFICATIONS	
Discharge temperature	From -20 to 65°C
Charging temperature	From 0 to 45°C

STORAGE SPECIFICATIONS	
Storage temperature	From -20 to 45°C
Storage voltage	From 52.4 V to 53.6 V


COMMUNICATIONS SPECIFICATIONS	
Bluetooth	No
Communication ports	2x RS485 | 2x Batt. Com. | 1x CAN
LCD screen	No
Volthium CAN Hub Communication (VE.CAN)	Compatible


Volthium
Alimentez le futur
Powering the future


NUMBER OF CYCLES ACCORDING TO THE AVERAGE DISCHARGE % OF USE	
30% discharge	8200 < cycles
80% discharge	6000 < cycles
100% discharge	3500 < cycles

MECHANICAL SPECIFICATIONS	
Dimensions	529.5 X 482.6 X 133 mm | 21 X 19 X 5.3 po
Group / format	3U
Weight	45.8kg | 101 lbs
Terminal Type	M10
Tightening torque on terminals	8~10nm / 6-8 ft/lb
Ingress protection rating	IP20 (Against solid objects larger than 12 mm)

CERTIFICATIONS & DESIGN	
Design	16S1P
Certifications	Module : Full ETL UL1973 3rd Edition, UL9540A. Full Battery Bank Certified UL9540
Shipping classification	UN 3480 | CLASS 9
Cell type	SquareCell - LiFePO4


Volthium
51.2-100-R
133


529.5
441
482.6


490
540